



SUPREME ANCHOR DIMENSIONS (inches)					
lb	A	B	C	D	E
5	13 ½	5 ½	9 ¾	8 ¾	8 ¼
10	17	7	12 ¼	10 ¾	10 ¼
15	18 ½	7 ¾	13 ¾	12 ¼	11
25	21 ¾	9 ¼	16 ¼	14 ¼	13 ¾
35	24 ½	10 ½	18 ¼	16 ¼	14
45	27	11 ½	20 ½	18	16 ¼
60	29 ½	12 ½	22 ½	18 ¾	17 ¾
80	33 ½	14 ¼	25 ½	22	19 ¾
100	35 ½	14 ½	26 ½	22	21
125	37 ¾	15 ¾	28 ¼	24 ½	23 ¼
150	40 ¼	16 ¼	29	25 ¾	24 ½
175	42 ¼	18	30 ¾	27	26 ½
225	43 ¼	18	32	28	27 ½
CUSTOM SIZING AVAILABLE UP TO 250kg (550lbs)					
PLEASE CONTACT FOR DIMENSIONS					

SUPREME ANCHOR DIMENSIONS (mm)					
Weight lb	A	B	C	D	E
5	340	140	250	225	210
10	430	175	310	275	260
15	470	195	350	310	285
25	550	235	415	360	350
35	620	265	465	415	360
45	685	295	520	460	410
60	750	315	570	485	450
80	850	360	650	560	500
100	905	370	675	560	525
125	960	400	715	620	600
150	1025	415	735	655	615
175	1075	455	780	685	675
225	1100	460	810	710	700
CUSTOM SIZING AVAILABLE UP TO 250kg (550lbs)					
PLEASE CONTACT FOR DIMENSIONS					

LLOYDS REGISTER OF SHIPPING APPROVED
 CERTIFIED AS AN **SHHP** ANCHOR
 SUPER HIGH HOLDING POWER
 CERTIFICATE NUMBER SPA- ANCH0062
 COMMUNITY DESIGN NO. 000483581-001
 US DESIGN PATENT APPLICATION no. 29/253,978
 COPYRIGHT 2005, 2006, 2007

IMPORTANT WARNING

**DRAWINGS NOT TO BE USED
 FOR CONSTRUCTION PURPOSES
 DIMENSIONS TO BE CONFIRMED
 BY MANSON BEFORE ORDERING**

	MANSON ANCHORS SUPREME ANCHOR FOR SIZING SEE TABLE	
	MATERIAL: PIN SAF 2205 STAINLESS STEEL 316L DIMENSIONS in mm tolerances +/- 0.3 unless otherwise stated	DATE: 25/11/06 SCALE: 1:75 @ A4 CHECKED: